

MOTOROMA

MOTOROMA engines are conceived specifically to respond to the needs of the PPG pilots. They are produced on the basis of parts, which are currently used in sports motorbikes. They consist of the highest durability parts. Our engines are covered by 2-year warranty for mechanical subassemblies. We ensure spare parts, technical inspections and post-warranty maintenance service.

JR180 ENGINE PARAMETERS

Displacement 175 cc
Manual pull start or electric start
Compression ratio 11:1
CDI ignition
Exhaust system with the resonance pipe
Max. power 26 hp (7500 rpm)
Laminar intake with a Walbro WB37 carburettor
Weight 14.7 kg (manual pull start) or 15.5 kg (electric start)



JR 350 ENGINE PARAMETERS

Engine type 2 stroke cycle boxer
Displacement 350 cc
Thrust 100 kG
Electric start
CDI ignition
Weight 25 kg (with two resonance pipes exhaust system)
An ideal engine for 2 person trike, powered sailplane or boat etc.

RK 180 ENGINE PARAMETERS

Displacement 182 cc
Manual pull start or electric start
Compression ratio 11:1
Electronic ignition
Exhaust system with the resonance pipe
Max. power 26 hp (7500 rpm)
Laminar intake with a Walbro WB37 carburettor
Weight 14.2 kg



CUSTOMER SERVICE AND SALE: SARABANDY STREET 73B, 02-868 WARSZAWA, POLAND
tel/fax +226449349 www.motoroma.eu e-mail motoroma@op.pl

MOTOROMA

PARAMOTOR PARAMETERS

MOTOROMA JR 180 engine - fasten on 4 reinforced gum shock absorbers.
1 or 2 ring, 1 to 5 part, removable aluminium cage - Ø 140 cm, with low fixed arms.
Kevlar propeller 124 cm
Fuel tank 13 l
Throttle grip with starter button and ignition kill switch.
DUDEK harness (with two elastic pockets on sides and a single cross-brace that can be fixed left or right side, depending on the propeller rotation - to neutralise torque).
Thrust 65-70 kg.
Weight 25 kg (electric start)



PARAMOTOR PARAMETERS

MOTOROMA RK 180 engine - fasten on 4 reinforced gum shock absorbers.
1ring, 1 to 5 part, removable aluminium cage - Ø 140 cm, with low fixed arms.
Kevlar propeller 124 cm
Fuel tank 13 l
Throttle grip with starter button and ignition kill switch.
DUDEK harness (with two elastic pockets on sides and a single cross-brace that can be fixed left or right side, depending on the propeller rotation - to neutralise torque).
Thrust 70 kg.
Weight 24,7 kg (electric start)

OUR PARAMOTORS ARE DESIGNED TO FLY A TRIKE!



CUSTOMER SERVICE AND SALE: SARABANDY STREET 73B, 02-868 WARSZAWA, POLAND
tel/fax +226449349 www.motoroma.eu e-mail motoroma@op.pl